



GTX

Heavy Duty Construction,
Highest Power Motors and
Handmade in America
Why Look Anywhere Else?



DRAIN SAVER
KEEPS DEBRIS OUT
OF DRAINS

36 VOLT SYSTEM
RUNS FOR FULL
SHIFT

**HEAVY DUTY
CONSTRUCTION
PREVENTS DAMAGE**

2 TANK SYSTEM
EASILY DRAIN
RECOVERY TANK

ROLLERS (6" TALL)
PROTECTS WALLS
AND KICK PLATES

HD FRONT DRIVE
CLIMB RAMPS

DISK OR CYLINDRICAL
SCRUB DECK



FACTORYCAT
INDUSTRIAL CLEANING EQUIPMENT



Scan This QR
Code With
Your Phone
For More
Information

www.factorycat.com
1 (800) 634-4060
(+001)262-681-3583



Series Scrubber Specifications

GTX

AUTHORIZED DISTRIBUTOR

BODY CONSTRUCTION / DIMENSIONS

Tank Material:	Poly 3/8" (10 mm)
Chassis Construction:	3/16" Steel (5 mm) Powder Coated Steel
Front Wheel (Diameter x Width):	10" x 3" (25 x 8 cm) - Solid Black
Rear Wheels (Diameter x Width):	(2x) 12" x 5" ([2x] 31 x 13 cm) - Solid Black
Size (L x W x H):	54" x 26" x 55" (137 x 66 x 140 cm)
Weight (w/o Batteries):	755 - 805 lbs (343 - 365 kg)
Weight (w/ 245 ah Batteries):	1,195 - 1,245 lbs (542 - 565 kg)

BRUSH / PAD SYSTEM

Disk Dimensions:	26" - (2x) 13" Diameter (66 - [2x] 33 cm)
<small>34 Inch Deck Includes HD Side Doors</small>	30" - (2x) 15" Diameter (76 - [2x] 38 cm)
	34" - (2x) 17" Diameter (86 - [2x] 43 cm)
Disk Motor:	(2x) 0.75 hp / 300 rpm ([2x] 559 watts)
Disk Brush Speed:	200 rpm
Cylindrical Dimensions:	24" - (2x) 5.25" x 22" (61 - [2x] 13 x 55.9 cm)
<small>5.25" Diameter Brush</small>	27" - (2x) 5.25" x 25" (69 - [2x] 13 x 64 cm)
<small>34 Inch Deck Includes HD Side Doors</small>	30" - (2x) 5.25" x 28" (76 - [2x] 13 x 71 cm)
	34" - (2x) 5.25" x 32" (86 - [2x] 13 x 81 cm)
Cylindrical Motor:	(2x) 0.75 hp / 350 rpm ([2x] 559 watts)
Cylindrical Brush Speed:	750 rpm
Actuator Rating:	500 lbs (227 kg)
Brush Pressure Settings:	(5) with Auto Adjust

POWER SYSTEM

System Voltage:	36 VDC
Standard Battery:	245 ah WET
Optional Battery:	325 ah WET / 360 ah WET / 250 ah AGM / 335 ah AGM
Run Time:	Up to 6.0 Hours*
<small>*Run times are based on continuous scrubbing run times.</small>	
Charger:	120VAC / 60 Hz Input - 36VDC / 25 amp Output

DRIVE SYSTEM:

Power:	0.75hp - All Gear / Sealed (559 watts)
Forward Speed:	0 - 320 ft/min (4 mph) 0 - 98 m/min (6 km/h)
Reverse Speed:	0 - 230 ft/min (3 mph) 0 - 70 m/min (5 km/h)

SOLUTION / RECOVERY SYSTEMS:

Solution Tank Capacity:	35 Gallons (133 liters) - w/ Graduated Site Tube
Solution Flow / Filter:	0 - 1.0 GPM / Stainless Inline (0 - 4 LPM)
Recovery Tank Capacity:	41 Gallons (155 liters) - 1.5" diameter Drain Hose
Demisting Chamber:	1.25 Gallons (5 liters)
Drain Saver:	30 cubic inches (492 cubic cm)
Vacuum Power:	1.0 hp / 3 Stage (740 watts)
Vacuum Specs (Water Lift / Airflow):	68" / 72 cfm (173 cm / 2 cm/m)
Squeegee:	26D - 32" Curved w/ 4-sided Rear Blade 30D, 24C, 27C, 30C - 35" Curved w/ 4-sided Rear Blade 34D, 34C - 38" Curved w/ 4-sided Rear Blade

GENERAL:

Cleaning Width:	26", 30" & 34" - Disk (66, 76 & 86 cm) 24", 27", 30", & 34" - Cylindrical (60, 69, 76, 86 cm)
Decibels:	67 dB
Productivity - Theoretical:	Up to 44,118 sqft (4,099 sqm)**
<small>**Productivity is based off of ISSA 2010 Cleaning Times</small>	
Productivity - Practical:	Up to 20,408 sqft (1,896 sqm)**
<small>**Productivity is based off of ISSA 2010 Cleaning Times</small>	
Seat with Switch Included	Headlights Included



www.factorycat.com
Phone: (800) 634-4060
International: (+001) 262-681-3583